

RD-R160 723


TRANS WORLD TIDAL GRAVITY PROFILE(U) INTERNATIONAL
CENTRE FOR EARTH TIDES BRUSSELS (BELGIUM) P MELCHIOR
31 DEC 84 AFGL-TR-85-0202 AFOSR-82-0097

1/1


UNCLASSIFIED

F/G 8/5

NL



END
FILED
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

AFGL-TR-85-0202

Q

AD-A160 723

TRANS WORLD TIDAL GRAVITY PROFILE

Paul Melchior


International Center for Earth Tides
Royal Observatory of Belgium
Avenue Circulaire, 3
B-1180 Brussels, Belgium

31 December 1984

Final Report
1 January 1984 - 31 December 1984

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

AIR FORCE GEOPHYSICS LABORATORY
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
HANSOM AIR FORCE BASE, MASSACHUSETTS 01731



DTIC FILE COPY

85 10 28 086

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. Report Number AFGL-TR-85-0202	2. Govt Accession No.	3. Recipient's Catalog Number
4. Title (and Subtitle) TRANS WORLD TIDAL GRAVITY PROFILE		5. Type of Report & Period Covered Final Scientific Report 1 January 1984 - 31 December 1984
		6. Performing Org. Report Number
7. Author(s) Professor Paul Melchior		8. Contract or Grant Number AFOSR 82-0097
9. Performing Organization Name and Address International Center for Earth Tides Royal Observatory of Belgium Avenue Circulaire, 3 B-1180 Brussels, Belgium		10. Program Element, Project, Task Area & Work Unit Numbers Program Element: 61102F Project/Task: 2309/G1 JOCAS: 2309G1AO
11. Controlling Office Name and Address Air Force Geophysics Laboratory/LWG Hanscom AFB, MA 01731		12. Report Date 31 December 1984
		13. Number of Pages 48
14. Monitoring Agency Name and Address European Office of Aerospace Research and Development/LSG Box 14 FPO New York 09510		15.
16. & 17. Distribution Statement Approved for public release; distribution unlimited.		
18. Supplementary Notes		
19. Key Words Gravity, Earth Tides, Coriolis Force, Gravimeter ✓		
20. Abstract The study analyzes 115 stations in the World Data Bank for Tidal Gravity. Under this study, 76 of these stations have been established in the equatorial and tropical regions as well as the Southern Hemisphere. This broad coverage has allowed, for the first time, for experimental determination of the Love numbers foreseen by Love (1911) and confirmed by Wahr (1981). This effect results from the flattening of the Earth and from the Coriolis force.		

International Center for Earth Tides
Centre international des Marées terrestres
(ICET)
(Federation of Astronomical and Geophysical Service, FAGS)

Director : P. MELCHIOR

Observatoire Royal de Belgique
Avenue Circulaire 3
B - 1180 Bruxelles, Belgium

Tel. 374 38 01
Telex Obabel 21546

Trans World Tidal Gravity Profile

Grant AFOSR 82-0097

Final Scientific Report

Period 1984 January 01 - 1984 December 31

1. - A most impressive result of this programme is that, in the World Data Bank for Tidal Gravity measurements recently established by Ducarme (1983), 115 stations amongst a world total of 238 have been installed and maintained and their registrations analysed in the frame of this "Trans World Tidal Gravity Profile" (83 according to the Table 1, plus a number of stations in Europe). Moreover, all the equatorial, tropical and southern hemisphere stations (except only 3 over a total of 76) are a result of this programme (see Figure 1, Table 1).
2. - This broad coverage over Europe, Asia, East and West Africa, Australia, South Pacific and South America (just started) has allowed, for the first time, to experimentally determine the latitude dependence of the Love numbers combination $\delta (= 1 + h - \frac{3}{2} k)$ foreseen by Love (1911) and firmly established by Wahr (1981). This effect results from the flattening of the Earth and from the Coriolis force. See Table 2.
3. - A carefull analysis of the data obtained in 1982-83 by us in China, Korea and Japan show that the Schwiderski map for the wave M_2 is to be slightly corrected near Taiwan and complemented by adding small polygons corresponding to the gulfs of Liantung and Petchili and the Korea Bay, a rather large area with strong but complicate tides (3 amphidromic points) which is not included in the Schwiderski model. (Figure 2).
We have completed the computations and obtained a general decrease of the amplitudes of the final residues \bar{X} (observed minus computed, see Figure 3), even in stations rather remote from the sea, of about 50 % that is less than one microgal everywhere except at Shanghai. (Table 3).
This shows that similar improvements should be made in a number of areas.
4. - We have shown that our series of measurements are so precise that a comparison can also be made at the level of 0.3 microgal ($3 \cdot 10^{-10}$ of g) with the Schwiderski cotidal maps of the small waves Q_1 and K_2 . This had, of course, never been done before.

85 10 28 086

5. - We have always strongly insisted upon the extreme importance of the instrumental phase lags determinations because most of the people, previously and even now, did not took care of it. However this correction is, very often, of the same size as the effect to be measured and it is not astonishing if it is impossible to reconcile such uncorrected measurements with the computations made for an earth model with oceans.

In this respect, an interesting experience was made in 1983 by us, in Japan, where a net of four tidal gravity stations gave experimental results in strong disagreement with the effects computed on the basis of Schwiderski maps. We have installed one of our meters, correctly calibrated, at Tokyo (one of the stations in this net) and, by direct comparison with the Japanese instrument obtained its instrumental constants. After the resulting correction the four stations results came in much better agreement with the computations (see Table 4).

These two results give us confidence in the correction of our operations - but this does not mean that controls are not necessary in the few stations where anomalies have been detected.

6. - The results reported on Table 2 show that, for the coefficients of the latitude terms, there is a fair agreement with the only theoretical model which includes earth's flattening and Coriolis force, i.e. the Wahr model.

However there is a discrepancy as large as 1 % on all the independent terms.

We decided to investigate that problem from both sides : theoretical and experimental.

The theoretical developments are presently under examination by one of my assistants Mrs Dehant who visited J. Wahr in 1984. Her work is progressing quite well but it is a long and hard task and we do not know the results yet.

The experimental research is developed along three different lines :

(a) - The transformation of all our LaCoste-Romberg gravimeters into zero method instruments by electrostatic feedback. This was made according to the Harrison-Sato procedure with some slight improvement introduced by Van Ruymbeke which makes the system valid whatever be the transducer plates positions. The analysis of several series in Bruxelles showed that this modification was fully successful. It has reconfirmed the validity of the rheological models previously used for the computations in the Trans World Profiles.

(b) - The construction, by Van Ruymbeke, of a very stable platform moving vertically by 2.15 cm at variable speeds (minimum period 200 s). The gravimeter is then calibrated with respect to the inertial force (maximum is 4 mgal) while the vertical gradient is eliminated by using the different speeds. The first experiments let hope to reach a precision of 0.1 % on amplitudes comparable with the tidal amplitudes (200 µgal).

(c) - The establishment of a European tidal gravity calibration line including 3 stations (figure 4) :

Kevo, Finland, latitude 69°45'
Subarctic Research Station

Bruxelles, Belgium, latitude 50°48'
Royal Observatory

Madrid, Spain, latitude 40°38'
Universidade Complutense

(Bruxelles being included to compare with the GWR Superconducting gravimeter and because series of more than 30 different instruments have already been performed there).

Three LaCoste-Romberg / zero method (402, 487, 665) have already been installed for periods of six months at each station.


The first analysis of these series tend to confirm the previous experimental results which should indicate the need for a correction to the Wahr model.

(Note : a short summary published in EOS 65, page 859, ref. G32-09 by Gwinn, Herring and Shapiro reports that, according to 4 years VLBI data, a small correction is to be applied to the Wahr nutation series. Such a correction should be in agreement with our tidal gravity measurements).

7. - The preliminary analysis of the data obtained in 1984 at 8 stations in South America, 5 stations in West Africa and the 3 stations of the european calibration line are reported hereafter.

At the end of 1984, despite the termination of this USAF contract, I have decided to maintain all the instruments in operation at the sites where they are. I have good hope to obtain small grants in 1985 from different sources in Belgium, in South America and from Unesco to maintain the operation for one more year. My plan is to have stations in 1985 at Lima (Peru), La Paz (Bolivia), Manaus, Rio Branco, Salvador (Brazil), Yaoundé (Cameroon), Franceville (Gabon) and Brazzaville (Congo).

May I hope that USAF could reconsider the possibility of a grant in 1986 to complete the nets in South America, West and Central Africa ...



STATIONS OPERATING IN 1984

The listings of the analysis of the registrations are given in Appendix for each of these stations.

1. South America

Curitiba (Brazil)

This station, situated at the Universidade Federal do Paraná, in the Instituto de Ciencias Geodésicas under Professor C. Gemael, has been chosen as fundamental station for intercomparison of all the instruments involved in the completion of the Brazilian tidal gravity network. It has been installed and revisited several times by Ducarme, Van Ruymbeke and Poitevin. In July 1984, M. Van Ruymbeke has transformed the three LaCoste Romberg instruments (n° 3, n° 8, n° 32 D) into zero method instruments. Series of measurements have been made before and after the transformations as shown on the following table :

Instrument	Number of hourly readings	Number of days	Efficiency coefficient
LCR 3 - original device -	1344	60	0.933
LCR 3Z - zero method -	1844	92	0.835
LCR 8 - original device -	1344	59	0.949
LCR 8Z - zero method -	1872	105	0.743
LCR 32 D - original device -	1920	85	0.941
LCR 32 DZ - zero method -	1920	92	0.870
GEOD 783 = paper recorder -	3792	174	0.908
GEOD 783 - cassette recorder -	2448	155	0.658

The many data obtained at Curitiba have been provisionally analysed and are still under consideration for definitive conclusions.

Vicosa (Brazil)

LCR 3

2736 readings within 166 days, efficiency : 0.687.
Maintenance is satisfactory but not excellent.

Santa Maria (Brazil) LCR 32 D

2832 readings obtained within 175 days, efficiency : 0.674.
Maintenance is satisfactory but not excellent.

Campo Grande (Brazil) LCR 8 + LCR 32

LCR 8 : 1824 readings obtained within 150 days, efficiency : 0.507.
We are not very happy with the results and, by the end of 1984, Poitevin has
installed LCR 32 (zero method) at the same place for a new series of measure-
ments which is now going on.

Goiania (Brazil) Grav. GEOD 783 established by Poitevin
3792 readings within 199 days, efficiency : 0.794.

Cuiaba (Brazil) Grav. GEOD 783 established by Poitevin in november
1984 operates with success. A first analysis has been made upon 48 days measu-
rements.

Caico (Brazil) Grav. LCR 8Z/ zero method, established by Poitevin
in december 1984. The first very preliminary results (23 days) show that it
operates correctly.

Santa Cruz (Bolivia) Grav. GEOD 84 established by Van Ruymbeke. This
instrument had to be installed to La Paz but the very low gravity could not be
reached within the range of this instrument. Van Ruymbeke moved then to Santa
Cruz where an important hospital is runned by belgian physicians who accepted
to maintain the instrument. Due to some difficulties we have analysed, up to
now, the 54 first days which are excellent. There was then a long interruption
but we have now succeeded to obtain about 40 more days of registration.
The maintenance is excellent, considering the special difficulties in that
region.

2. West Africa

Lamto (Ivory Coast) Grav. GEOD 765 established by Van Ruymbeke.

3264 readings within 145 days, efficiency : 0.938.

The site was excellent and the staff also. Our station was under the responsibility of Mr Tounier, the founder of the LAMTO Observatory.

Niamey (Niger) Grav. LCR 336Z, zero method, established by

Van Ruymbeke.

2208 readings within 133 days, efficiency : 0.692.

A station difficult to maintain as often in West Africa.

Arlit (Niger) Grav. LCR 336Z (zero method), established by

Van Ruymbeke.

1920 readings within 138 days, efficiency : 0.580.

This was a very difficult station to install and to maintain because of several "obvious" reasons. It was maintained by catholic missionaries. The equipment had to be taken back by the Ambassador of Belgium himself ...

Ouagadougou (Burkina Faso/Upper Volta) Grav. GEOD 765 established by

Van Ruymbeke.

2688 readings within 142 days, efficiency : 0.789.

A station difficult to maintain as often in West Africa.

Bangui (Centrafricaine) gravimeters GEOD 765 and LCR 336 Z (zero method) established by Ducarme by the end of 1984 to obtain a long series of simultaneous registration. We have much hope because the site is excellent.

3. European Calibration Line

Kevo (Finland) Simultaneous recording with two La Coste Romberg model G, zero method : 402, 665 (six months each).

Bruxelles (Belgium) GWR Superconducting gravimeter in continuous operation since.

Madrid (Spain) Simultaneous recording with two La Coste Romberg model G, zero method : 402, 487 (four months each).




Figure 1 : Trans World Tidal Gravity Profile
ICET 1973 - 1984




Figure 2 : Areas added or modified in the Schwiderski maps.

$A \sin \alpha$




Figure 3

\vec{A} observed vector (A : amplitude, α : phase)

\vec{R} tidal vector for an elastic non-viscous earth with liquid core but oceanless (R : amplitude, zero phase)

\vec{L} ocean attraction and loading vector (L : amplitude, λ : phase)

$\vec{B} = \vec{A} - \vec{R}$ (B : amplitude, β : phase)

$\vec{X} = \vec{B} - \vec{L}$ (X : amplitude, x : phase)

For the semi-diurnal wave M_2 , the correct scale of this figure should be on the order of

$R \sim A \sim 400 \text{ nms}^{-1}$ (Europe) to 900 nms^{-1} (Equatorial zone)

$\alpha \sim 0^\circ$ to $\pm 5^\circ$

$L \sim B \sim 20$ to 100 nms^{-1}

$\epsilon \sim 5 \text{ nms}^{-1}$ (Europe) to 10 nms^{-1} (Equatorial zone)




Figure 4.




Figure 5 : Tidal gravity stations (TWP) in Brazil

■ operating stations in 1984

~~~ stations to be installed in 1985

isolines : amplitude of the oceanic tidal effect, wave  $M_2$ , in microgals.

TABLE 1

## PROFIL MONDIAL DE MAREES TERRESTRES

1973 - 1984 : 83 stations (six months measurements).

## SIA (32 stations)

SOUTH PACIFIC (20 stations)

|            |               |                   |                |              |
|------------|---------------|-------------------|----------------|--------------|
| Inbul      | - Turkey      | Banjar Baru       | Helwan         | Curitiba (4) |
| ra (*)     |               | Bandung           | Aewan          | Santa Maria  |
| iz         | - Iran        | Makassar          |                | Vicos        |
| ran        |               | Jaya Pura         | - Indonesia    | Campo Grande |
| awar       |               | Timor             |                | Brazil       |
| ta         | - Pakistan    | Port Moresby      | - Papua        | Goiania      |
| re         |               | Darwin            |                | Cuiaba       |
| rabad      | - India       | Perth             |                | Caico        |
| mandu (2)  | - Nepal       | Alice Springs (*) |                |              |
| mbo        | - Sri Lanka   | Broken Hill       | - Australia    |              |
| ng Mai (2) |               | Canberra (*) (4)  |                |              |
| kok        | - Thailand    | Charters Towers   |                |              |
| ng         |               | Hobart            |                |              |
| a Lumpur   | - Malaysia    | Hamilton          | - New Zealand  |              |
| Kinabalu   |               | Lauder            |                |              |
| la         | - Philippines | Noumea            | - N. Caledonia |              |
| g Tao      |               | Suva              | - Fiji         |              |
| yang       |               | Apia              | - Samoa        |              |
| ing        |               | Papeete           | - Tahiti       |              |
| hou (*)    |               |                   |                |              |
| chi        | - China       |                   |                |              |
| n (*) (4)  |               |                   |                |              |
| ing        |               |                   |                |              |
| on         |               |                   |                |              |
| ghai       |               |                   |                |              |
| Kong       |               |                   |                |              |
| o          |               |                   |                |              |
| mbetsu     | - Japan       |                   |                |              |
| sawa       |               |                   |                |              |
| o          |               |                   |                |              |
| ya         |               |                   |                |              |

SOUTH AMERICA (8 stations)

|               |                  |  |  |  |
|---------------|------------------|--|--|--|
| Curitiba (4)  |                  |  |  |  |
| Santa Maria   |                  |  |  |  |
| Vicos         |                  |  |  |  |
| Campo Grande  |                  |  |  |  |
| Brazil        |                  |  |  |  |
| Goiania       |                  |  |  |  |
| Cuiaba        |                  |  |  |  |
| Caico         |                  |  |  |  |
| Nairobi       |                  |  |  |  |
| Voi           |                  |  |  |  |
|               |                  |  |  |  |
| Dar es Salaam | - Tanzania       |  |  |  |
| Butare        | - Rwanda         |  |  |  |
| Harare        | - Zimbabwe       |  |  |  |
| Nampula       | - Mozambique     |  |  |  |
| Maputo        |                  |  |  |  |
| Arta          | - Djibouti       |  |  |  |
| Antananarivo  | - Madagascar     |  |  |  |
| Tolagnaro     |                  |  |  |  |
| Nossi Bé      |                  |  |  |  |
| Johannesburg  | - South Africa   |  |  |  |
| Stellenbosch  |                  |  |  |  |
|               |                  |  |  |  |
| Lamto         | - Ivory Coast    |  |  |  |
| Niamey        |                  |  |  |  |
| Arlit         |                  |  |  |  |
| Ouagadougou   | - Bourkiné Fasso |  |  |  |
| Bangui        | - Centrafrica    |  |  |  |

(\*) stations with more than six months measurements.

(n) number of different instruments used.

- Korea

1

Table 2Diurnal waves

$$x_1 = Y_4^1 / Y_2^1 = \frac{\sqrt{6}}{4} (7 \sin^2 \phi - 3)$$

$\Omega_1$  W  $\delta = 1.1520 - 0.0063 x_1$

MB  $\delta = 1.1618 - 0.0028 x_1$   
 $\pm 16 \quad \pm 15$

$P_1$  W  $\delta = 1.1470 - 0.0063 x_1$

MB  $\delta = 1.1522 - 0.0039 x_1$   
 $\pm 29 \quad \pm 29$

$K_1$  W  $\delta = 1.1320 - 0.0063 x_1$

MB  $\delta = 1.1458 - 0.0059 x_1$   
 $\pm 12 \quad \pm 13$

Semi-Diurnal waves

$$x_2 = Y_4^2 / Y_2^2 = \frac{\sqrt{3}}{2} (7 \sin^2 \phi - 1)$$

W  $\delta = 1.1599 - 0.0045 x_2$

MB  $\delta = 1.1751 - 0.0046 x_2$   
 $\pm 21 \quad \pm 10$

W : Wahr theoretical result

MB : Melchior-De Becker experimental result

TABLE 3 Final residue  $\vec{X} = \vec{B} - \vec{L} + \vec{A} - \vec{R} - \vec{L}$  (see fig. 1)

|              | Schwiderski map |        | Schwiderski map with additions and corrections |       |
|--------------|-----------------|--------|------------------------------------------------|-------|
| <u>China</u> | X               | X      | X                                              | X     |
| Shenyang     | 0.88            | -60.5  | 0.30                                           | 7.6°  |
| Beijing      | 0.60            | -10.4  | 0.60                                           | 63.8  |
| Tsing Tao    | 1.57            | -48.4  | 0.85                                           | 73.7  |
| Lanzhou      | 0.74            | -55.7  | 0.48                                           | -54.3 |
| Urumqi       | 0.67            | -11.9  | 0.56                                           | -9.3  |
| Wuhan        | 0.61            | -71.3  | 0.14                                           | 39.3  |
| Shanghai     | 1.74            | -128.0 | 1.68                                           | 99.9  |
| Kunming      | 1.05            | -27.8  | 0.86                                           | -20.9 |
| Guangzhou    | 0.37            | -151.4 | 0.44                                           | 147.8 |
| <u>Korea</u> |                 |        |                                                |       |
| Séoul        | 1.32            | 10.4   | 0.52                                           | 46.5  |
| <u>Japan</u> |                 |        |                                                |       |
| Kanoya       | 1.33            | -105.3 | 0.30                                           | -64.3 |
| Kyoto        | 0.46            | -126.3 | 0.04                                           | 133.1 |
| Mean residue | 0.95 microgal   |        | 0.56 microgal                                  |       |

The amplitudes are given in microgals ( $\sim 10^{-9}$  of g).

TABLE 4      Readjustment of Japanese data by comparison  
with our series of registration at Tokyo station

| Stations                  | Observed Residues |      |       |      | Calculated Residues<br>according to<br>Schwiderski maps |     |
|---------------------------|-------------------|------|-------|------|---------------------------------------------------------|-----|
|                           | A                 |      | B     |      |                                                         |     |
| <u>M<sub>2</sub> wave</u> |                   |      |       |      |                                                         |     |
| Fujigawa                  | 5.15              | -11° | 2.65  | 12°  | 2.59                                                    | 19° |
| Yatsugatake               | 3.88              | -17° | 1.41  | 15°  | 2.03                                                    | 23° |
| Yashiko                   | 4.30              | - 7° | 2.15  | 24°  | 1.63                                                    | 32° |
| Tokyo                     | 3.86              | -14° | (2.51 | 20°) | 2.33                                                    | 27° |
| <u>O<sub>1</sub> wave</u> |                   |      |       |      |                                                         |     |
| Fujigawa                  | 3.84              | -10° | 2.35  | - 6° | 2.05                                                    | 14° |
| Yatsugatake               | 2.39              | 3°   | 1.07  | 26°  | 1.81                                                    | 15° |
| Yashiko                   | 3.26              | - 7° | 1.77  | - 1° | 1.66                                                    | 18° |
| Tokyo                     | 2.97              | - 4° | (2.05 | 7°)  | 2.04                                                    | 16° |

A Japanese solution

B ICET solution when the gravimeter LCR 34 is corrected by comparison with  
GEOID 783 at Tokyo.

Amplitudes are given in microgals ( $\sim 10^{-9}$  of g).

## Published papers

- De Becker, M. and Ducarme, B. : 1983, Sampling and Preprocessing of tidal data at one minute interval.  
IUGG General Assembly, Hamburg - IAG Commission on Earth Tides.  
Bull. Inf. Marées Terrestres 91 : 5992-6000.
- Ducarme, B. : 1975, A fundamental station for trans-world tidal gravity profiles.  
Phys. Earth Planet. Inter., 11 : 119-127.
- Ducarme, B. : 1983a, A Data Bank for Earth Tides.  
IUGG General Assembly, Hamburg - Symposium 6 : Data Management.  
Bull. Inf. Marées Terrestres 91 : 5963-5980.
- Ducarme, B. : 1983b, Tidal gravity parameters at Brussels reconfirmed by a superconducting gravimeter.  
Phys. Earth Planet. Inter., 32 : 1-3.
- Ducarme, B. and Melchior, P. : 1978, A Trans-world tidal gravity profile.  
Phys. Earth Planet. Inter., 16 : 257-276.
- Melchior, P. : 1981, An effect of the earth ellipticity and inertial forces is visible from  $M_2$  and  $O_1$  tidal gravity measurements in the Trans World Profiles.  
9th Intern. Symposium on Earth Tides, New York, Comm. Obs. R. Belg., A 63, S. Geoph. 141 : 1-9.
- Melchior, P., Moens, M. and Ducarme, B. : 1980, Computations of tidal gravity loading and attraction effects.  
Bull. Obs. Marées Terrestres, Obs. R. Belg. 4, fasc. 5 : 1-94.
- Melchior, P., Moens, M., Ducarme, B. and Van Ruymbeke, M. : 1981, Tidal loading along a profile Europe - East Africa - South Asia - Australia and the Pacific Ocean.  
Phys. Earth Planet. Inter., 25 : 71-106.
- Melchior, P. and De Becker, M. : 1983, A discussion of world-wide measurements of tidal gravity with respect to oceanic interactions, lithosphere heterogeneities, Earth's flattening and inertial forces.  
Phys. Earth Planet. Inter., 31 : 27-53.
- Melchior, P., Ducarme, B. and Chueca, R.M. : 1983a, The small tidal waves  $Q_1$  and  $K_2$  as an evidence of the accuracy of the trans world tidal gravity measurements.  
IUGG General Assembly, Hamburg - IAG Commission on Earth Tides.  
Bull. Inf. Marées Terrestres 91 : 5981-5986.
- Melchior, P., De Becker, M., Ducarme, B., Poitevin, Ch. and Van Ruymbeke, M. : 1983b, Effect of lateral heterogeneities in the lithosphere on tidal measurements.  
IUGG General Assembly, Hamburg - IAG Commission on Earth Tides.  
Bull. Inf. Marées Terrestres 91 : 5987-5991.
- Melchior, P., Ducarme, B., Van Ruymbeke, M., Poitevin, Ch. and De Becker, M. : 1984, Interactions between oceanic and gravity tides, as analysed from world-wide earth tide observations and ocean models.  
Marine Geophysical Researches, vol. 7, pp. 77-91.
- Melchior, P., Ducarme, B., Van Ruymbeke, M. and Poitevin, Ch. : 1984, Trans World Tidal gravity profiles.  
Observ. Roy. Belgique - Bulletin d'Observations - Marées Terrestres - vol. V, fasc. 1, 102 pages.

## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE - BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEODESIA-U.F.P.R. PROF. C.GEMAELE  
 GRAVIMETRE GEODYNAMICS 783 P.MELCHIOR - OBSERVATOIRE ROYAL DE BELGIQUE  
 CALIBRATION BRUXELLES - FUNDAMENTAL STATION/NC50.4V/  
 INSTALLATION E.DUCARME,C.GEMAELE,J.BITTENCOURT,MILTON CAMPOS  
 MAINTENANCE C.GEMAELE,J.BITTENCOURT,MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 24/10/29

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .95339

PHASE LAG .01 .415 M2 .844 01/M2 .492

CORRECTION FOR ATTENUATION 01 1.00003 M2 1.00011 /MODEL 1/

G783 8311 6/831116 831120/8312 4 8312 8/8312 8 831212/84 1 3 84 1 6/84 124  
 G783 64 128/84 213 84 218/84 218 84 221/84 225 84 229/84 425

TIME INTERVAL 173.5 DAYS 3792 READINGS 9 BLOKS

| WAVE GROUP<br>ARGUMENT | N  | WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. PHASE |
|------------------------|----|------|---------------------------|-----------------|--------|----------------|--------|------------------------|
| 133.-136.              | 20 | Q1   | 5.66 .07                  | 1.2268          | .0160  | -.204          | .750   | .31 176.3              |
| 143.-145.              | 16 | O1   | 28.57 .07                 | 1.1855          | .0030  | -1.379         | .146   | .93 132.2              |
| 152.-155.              | 15 | N01  | 2.35 .06                  | 1.2408          | .0320  | 1.316          | 1.478  | .16 -160.8             |
| 161.-163.              | 10 | P1   | 12.65 .07                 | 1.1280          | .0066  | .282           | .335   | .29 -12.2              |
| 164.-168.              | 23 | S1K1 | 39.04 .07                 | 1.1519          | .0021  | .084           | .105   | .49 -173.2             |
| 175.-177.              | 14 | J1   | 2.25 .07                  | 1.1897          | .0381  | -2.172         | 1.838  | .10 121.4              |
| 184.-186.              | 11 | 001  | 1.18 .06                  | 1.1385          | .0565  | -4.213         | 2.835  | .09 73.3               |
| 233.-23X.              | 20 | 2N2  | 2.26 .03                  | 1.2080          | .0185  | 4.652          | .882   | .20 65.8               |
| 243.-248.              | 24 | N2   | 14.12 .05                 | 1.2053          | .0038  | 2.045          | .182   | .72 44.0               |
| 252.-258.              | 26 | M2   | 71.86 .04                 | 1.1744          | .0007  | 1.759          | .036   | 2.36 69.2              |
| 265.-265.              | 9  | L2   | 2.00 .04                  | 1.1545          | .0209  | .903           | 1.032  | .03 107.5              |
| 267.-273.              | 9  | S2   | 33.29 .04                 | 1.1696          | .0015  | 1.953          | .071   | 1.16 77.5              |
| 274.-277.              | 12 | K2   | 8.89 .04                  | 1.1476          | .0050  | 2.322          | .246   | .37 106.1              |
| 335.-375.              | 16 | M3   | 1.21 .02                  | 1.1132          | .0228  | .432           | 1.159  | .05 10.4               |

STANDARD DEVIATION D 2.96 SD 1.70 TD .93 MICROGAL  
 01/K1 1.0291 1-01/1-K1 1.2210 M2/01 .9906  
 CENTRAL EPOCH TJJ= 2445730.0

## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEOESIA-U.F.PR. PPOF. C.GEMAEL  
 TRANS WORLD TIDAL GRAVITY PROFILES P. MELCHIOR  
 GRAVIMETRE LA COSTE ROMBERG 3 ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMEKE  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION CURITIBA - STATION FONDAMENTALE  
 INSTALLATION M. VAN RUYMEKE, E. RATTON  
 MAINTENANCE C.GEMAEL, J.BITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING E.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 65/ 3/20

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR .98829

G 3 84 729/84 8 2 84 8 8/84 818 84 822/84 9 1 84 9 5/84 917 84 921/84 929  
 G 3 8410 5/8410 9 841013/841027

TIME INTERVAL 92.5 DAYS 1824 READINGS 7 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | PESIDUE<br>AMPL. - PHASE |           |
|------------------------|--------|---------------------------|-----------------|--------|----------------|--------|--------------------------|-----------|
| 133.-139. 30           | Q1     | 5.49                      | .23             | 1.1890 | .0498          | -1.472 | 2.402                    | .19 133.6 |
| 143.-149. 26           | 01     | 28.47                     | .26             | 1.1813 | .0106          | -1.423 | .516                     | .88 126.4 |
| 161.-168. 33           | P1S1K1 | 37.60                     | .29             | 1.1094 | .0086          | -1.315 | .450                     | 1.29 41.8 |
| 243.-248. 24           | N2     | 13.99                     | .15             | 1.1940 | .0132          | 2.346  | .619                     | .69 56.1  |
| 252.-258. 26           | M2     | 71.86                     | .16             | 1.1744 | .0027          | 1.406  | .132                     | 1.96 64.1 |
| 267.-277. 21           | S2K2   | 33.94                     | .13             | 1.1924 | .0047          | 2.946  | .223                     | 1.95 63.4 |
| 335.-375. 16           | M3     | 1.36                      | .07             | 1.2552 | .0599          | 3.134  | 2.693                    | .22 20.2  |

STANDARD DEVIATION D 7.00 SD 4.01 TD 1.78 MICROGAL  
 01/K1 1.0648 1-01/1-K1 1.6568 M2/01 .9942  
 CENTRAL EPOCH TJJ= 2445956.0

TRANS WORLD PROFILE

SOUTH AMERICA

STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 GRAVIMETRE LA COSTE ROMBERG 3 TRANS WORLD TIDAL GRAVITY PROFILES P.MELCHIOR  
 CALIBRATION CURITIBA - STATION FONDAMENTALE  
 INSTALLATION C.POITEVIN, E.RATTON  
 MAINTENANCE C.GEMAEL, J.EITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .91554

PHASE LAG Q1 2.390 M2 2.268 C1/M2 1.054

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/Q1 1.03C78 /MODEL 2/

6 3 84 523/84 529 84 6 2/84 624 E4 628/84 720

TIME INTERVAL 60.0 DAYS 1344 READINGS 3 BLOKS

| WAVE GROUP<br>ARGUMENT       | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOF | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE |
|------------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|-------|
| 133.-139. 30 Q1              |           | 5.85 .37                  | 1.2669          | .0807  | -.616          | 3.622  | .50              | 172.8 |
| 143.-149. 26 01              |           | 28.87 .30                 | 1.1982          | .0123  | -1.165         | .593   | 1.10             | 147.8 |
| 161.-168. 33 P1S1K1          | 39.12 .25 |                           | 1.1542          | .0074  | -1.776         | .363   | 1.33             | 114.2 |
| 243.-248. 24 N2              |           | 14.72 .24                 | 1.2567          | .0203  | 3.647          | .954   | 1.45             | 40.4  |
| 252.-258. 26 M2              |           | 71.86 .19                 | 1.1745          | .0030  | 1.361          | .152   | 1.91             | 63.3  |
| 267.-277. 21 S2K2            |           | 34.47 .25                 | 1.2109          | .0087  | 1.401          | .417   | 1.67             | 30.4  |
| 335.-375. 16 M3              |           | 1.31 .19                  | 1.2101          | .1775  | -7.667         | 8.719  | .23              | -50.7 |
| STANDARD DEVIATION D         |           | 7.21                      | SD              | 4.09   | TD             | 4.27   | MICROGAL         |       |
| Q1/K1 1.0381                 | 1-C1/1-K1 | 1.2852                    | M2/C1           | .9802  |                |        |                  |       |
| CENTRAL EPOCH TJJ= 2445872.0 |           |                           |                 |        |                |        |                  |       |

|                                                                          |                                        |                  |
|--------------------------------------------------------------------------|----------------------------------------|------------------|
| TRANS WORLD PROFILE                                                      | SOUTH AMERICA                          | STATION CURITIBA |
| STATION 7305 CURITIBA PARANA                                             | COMPOSANTE VERTICALE                   | BRESIL           |
| 25 27 15.3S 49 14 15.6W                                                  | H 913M P 3M                            | O 80KM           |
| CENTRO POLITECNICO-GEODEZIA-U.F.PR.                                      | PROF. C.GEMAEL                         | :                |
| TRANS WORLD TIDAL GRAVITY PROFILES                                       | P. MELCHIOR                            | :                |
| GRAVIMETRE LACOSTE ROMEIRG 8 ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMBEKE |                                        |                  |
| AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON                        |                                        |                  |
| CALIBRATION                                                              | CURITIBA - STATION FONDAMENTALE        |                  |
| INSTALLATION                                                             | M. VAN RUYMBEKE, E. RATTON             |                  |
| MAINTENANCE                                                              | C.GEMAEL, J.BITTENCOURT, MILTON CAMPOS |                  |

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING E.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/20

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR 1.00230

G 8 84 729/84 8 6 84 6 9/84 9 6 84 922/84 924 84 929/84 929 8410 3/841013  
 G 8 841017/841029 8411 5/8411 9

| TIME INTERVAL                | 105.0 DAYS      | 1872 READINGS | 7 BLOKS |              |                        |
|------------------------------|-----------------|---------------|---------|--------------|------------------------|
| WAVE GROUP                   | ESTIMATED AMPL. | AMPL.         | PHASE   | PESIDUE      |                        |
| ARGUMENT                     | N WAVE          | R.M.S.        | FACTOR  | R.M.S.       | AMPL. PHASE            |
| 133.-139.                    | 30 Q1           | 5.48          | .18     | 1.1668 .0385 | .094 1.270 .13 -175.9  |
| 143.-149.                    | 26 01           | 28.27         | .19     | 1.1732 .0080 | -1.165 .389 .66 119.9  |
| 161.-168.                    | 33 P1S1K1       | 39.09         | .21     | 1.1536 .0063 | -0.395 .314 .60 153.5  |
| 243.-248.                    | 24 N2           | 13.58         | .18     | 1.1590 .0157 | .969 .771 .23 93.7     |
| 252.-258.                    | 26 M2           | 71.85         | .20     | 1.1744 .0033 | 1.347 .160 1.89 63.2   |
| 267.-277.                    | 21 S2K2         | 33.34         | .16     | 1.1711 .0058 | 1.603 .279 .98 72.1    |
| 335.-375.                    | 16 M3           | 1.20          | .06     | 1.1031 .0590 | -1.824 3.028 .05 -44.9 |
| STANDARD DEVIATION           | D               | 5.49          | SD      | 5.10         | TD 1.76 MICROGAL       |
| 01/K1                        | 1.0170          | 1-01/1-K1     | 1.1279  | M2/01        | 1.0009                 |
| CENTRAL EPOCH TJJ= 2445962.0 |                 |               |         |              |                        |

## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEI  
 GRAVIMETRE LA COSTE ROMBERG 8 TRANS WORLD TIDAL GRAVITY PROFILES P.MELCHIOR  
 CALIBRATION CURITIBA - STATION FONDAMENTALE  
 INSTALLATION C.POITEVIN,E.RATTON  
 MAINTENANCE C.GEMAEI,J.BITTENCOURT,MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR .96620

PHASE LAG O1 1.366 M2 1.633 O1/M2 .836

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/O1 1.01912 /MODEL 2/

G E 64 560/24 6 9 84 614/84 722

TIME INTERVAL 59.0 DAYS 1344 READINGS 2 BLOCKS

| WAVE GROUP<br>ARGUMENT | N. WAVE   | ESTIMATED AMPL.<br>P.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139.              | 30 Q1     | 6.23 .41                  | 1.3510          | .0891  | -.811          | 3.766  | .89              | 174.3  |
| 143.-149.              | 26 01     | 26.30 .34                 | 1.1746          | .0140  | -1.165         | .686   | .68              | 122.2  |
| 161.-168.              | 33 P1S1K1 | 38.43 .28                 | 1.1341          | .0083  | -.056          | .414   | .13              | 17.5   |
| 243.-248.              | 24 N2     | 15.17 .31                 | 1.2950          | .0266  | 2.331          | 1.200  | 1.68             | 21.5   |
| 252.-258.              | 26 M2     | 71.86 .25                 | 1.1744          | .0041  | 1.361          | .203   | 1.91             | 63.4   |
| 267.-277.              | 21 S2K2   | 34.03 .34                 | 1.1954          | .0119  | 1.840          | .572   | 1.47             | 47.9   |
| 335.-375.              | 16 M3     | 1.14 .10                  | 1.0489          | .0883  | -12.186        | 4.920  | .24              | -100.8 |

STANDARD DEVIATION D 8.34 SD 5.50 TD 2.11 MICROGAL

O1/K1 1.0357 1-01/1-K1 1.3019 M2/01 .9999

CENTRAL EPOCH TJJ= 2445875.0

## TRANS WORLD PROFILE

## SOUTH AMERICA

**STATION CURITIBA**

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 TRANS WORLD TIDAL GRAVITY PROFILES P. MELCHIOR  
 GRAVIMETRE LACOSTE ROMBERG D 32 ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMBEKE  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION CURITIBA - STATION FONDAMENTALE  
 INSTALLATION M. VAN RUYMBEKE, E. RATTON  
 MAINTENANCE C.GEMAEL, J.EITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING E.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FACGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/20

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR .99592

6 32 64 729/84 8 4 84 812/84 925 8410 3/841027

TIME INTERVAL 92.5 DAYS 1920 READINGS 3 BLOKS

## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 60KM  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 GRAVIMETRE LA COSTE ROMBERG D32 TRANS WORLD TIDAL GRAVITY PROFILES P.MELCHIOR  
 CALIBRATION CURITIBA - STATION FONDAMENTALE  
 INSTALLATION C.POITEVIN, E.RATTON  
 MAINTENANCE C.GEMAEL, J.BITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .92619

PHASE LAG Q1 2.249 M2 1.381 Q1/M2 1.629

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/Q1 1.01747 /MODEL 2/

6 32 84 430/84 5 4 84 510/84 6 9 84 613/84 623 84 628/84 7 6 84 710/84 720

TIME INTERVAL 83.0 DAYS 1728 READINGS 5 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | PESIDUE<br>AMPL. | PHASE |
|------------------------|--------|---------------------------|-----------------|--------|----------------|--------|------------------|-------|
| 133.-139. 30 Q1        |        | 5.47 .19                  | 1.1850          | .0409  | -2.067         | 1.983  | .23              | 119.8 |
| 143.-149. 26 Q1        |        | 28.22 .16                 | 1.1712          | .0067  | -1.165         | .326   | .64              | 116.0 |
| 161.-168. 33 P1S1K1    |        | 38.95 .14                 | 1.1493          | .0040  | -1.149         | .197   | .87              | 116.4 |
| 243.-248. 24 N2        |        | 14.07 .12                 | 1.2007          | .0104  | .491           | .504   | .49              | 14.2  |
| 252.-258. 26 M2        |        | 71.85 .10                 | 1.1744          | .0017  | 1.361          | .082   | 1.91             | 63.5  |
| 267.-277. 21 S2K2      |        | 33.45 .12                 | 1.1751          | .0042  | 2.247          | .202   | 1.37             | 73.0  |
| 335.-375. 16 M3        |        | 1.28 .12                  | 1.1759          | .1124  | 4.240          | 5.549  | .15              | 39.5  |

STANDARD DEVIATION D 4.41 SD 2.49 TD 3.06 MICROGAL

Q1/K1 1.0190 1-Q1/1-K1 1.1467 M2/01 1.0027

CENTRAL EPOCH TJJ= 2445861.0

TRANS WORLD PROFILE

SOUTH AMERICA

STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE BRESIL  
 25 27 15.3S 49 14 15.6W H 913M P 3M D 80KM  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 GRAVIMETRE LA COSTE ROMBERG D 99 ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMBEKE  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 INSTALLATION M. VAN RUYMBEKE, E. RATTON  
 MAINTENANCE C.GEMAEL, J.BITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/20

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR 1.10496

G 99 84 729/84 8 6 84 8 9/84 223 84 826/84 9 7 84 927/84 929 8410 3/841025

TIME INTERVAL 90.5 DAYS 1632 READINGS 5 BLOKS

| WAVE GROUP<br>ARGUMENT        | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE |
|-------------------------------|-----------|---------------------------|-----------------|-----------------|--------|----------------|--------|------------------|-------|
| 133.-139.                     | 30 Q1     | 5.63                      | .20             | 1.2202          | .0443  | -2.583         | 2.075  | .37              | 137.3 |
| 143.-149.                     | 26 01     | 28.66                     | .23             | 1.1895          | .0094  | -.653          | .452   | .80              | 155.7 |
| 161.-168.                     | 33 P1S1K1 | 38.91                     | .25             | 1.1482          | .0074  | -1.063         | .373   | .80              | 116.0 |
| 243.-248.                     | 24 N2     | 14.15                     | .19             | 1.2078          | .0163  | 2.798          | .771   | .88              | 51.9  |
| 252.-258.                     | 26 M2     | 71.86                     | .21             | 1.1744          | .0034  | 1.323          | .164   | 1.87             | 62.7  |
| 267.-277.                     | 21 S2K2   | 33.24                     | .17             | 1.1676          | .0061  | 1.675          | .292   | 1.11             | 79.7  |
| 335.-375.                     | 16 M3     | 1.24                      | .09             | 1.1395          | .0858  | 1.117          | 4.257  | .08              | 17.2  |
| STANDARD DEVIATION            |           | D                         | 6.09            | SD              | 5.03   | TD             | 2.39   | MICROGAL         |       |
| Q1/K1                         |           | 1.0359                    | 1-01/1-K1       | 1.2785          | M2/01  | .9873          |        |                  |       |
| CENTRAL EPOCH TUJ = 2445955.0 |           |                           |                 |                 |        |                |        |                  |       |

TRANS WORLD PROFILE

SOUTH AMERICA

STATION CURITIBA

STATION 7305 CURITIBA PARANA COMPOSANTE VERTICALE  
 25 27 15.3S 49 14 15.6W H 913M P 3M BRESIL  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 GRAVIMETRE LA COSTE ROMBERG MODELE D 99  
 INSTALLATION E. RATTON  
 MAINTENANCE C.GEMAEL, J.BITTENCOURT, MILTON CAMPOS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .99022

PHASE LAG Q1 5.385 M2 4.391 Q1/M2 1.228

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/Q1 1.06289 /MODEL 2/

6 99 84 521/84 612 84 618/84 626 84 7 6/84 710 84 714/84 714 84 722/84 724

TIME INTERVAL 66.5 DAYS 1104 READINGS 5 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|--------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139. 30 Q1        |        | 5.57 1.18                 | 1.2064          | .2563  | 8.862          | 11.975 | .87              | -99.9  |
| 143.-149. 26 01        |        | 26.33 .92                 | 1.1755          | .0384  | -1.165         | 1.864  | .69              | 123.7  |
| 161.-168. 33 P1S1K1    |        | 38.52 .73                 | 1.1365          | .0215  | -2.299         | 1.073  | 1.55             | 87.5   |
| 243.-248. 24 N2        |        | 15.24 1.14                | 1.3008          | .0972  | 11.849         | 4.513  | 3.40             | 67.1   |
| 252.-258. 26 M2        |        | 71.86 .89                 | 1.1744          | .0145  | 1.361          | .748   | 1.91             | 63.4   |
| 267.-277. 21 S2K2      |        | 32.26 1.05                | 1.1332          | .0367  | -2.644         | 1.960  | 1.69             | -118.3 |
| 335.-375. 16 M3        |        | 1.39 .47                  | 1.2766          | .4289  | 11.779         | 20.807 | .35              | 55.0   |

STANDARD DEVIATION D 17.89 SD 15.07 TD 9.28 MICROGAL  
 01/K1 1.0343 1-01/1-K1 1.2853 M2/01 .9991  
 CENTRAL EPOCH TJJ= 2445874.0



## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION CAMPO GRANDE

STATION 7307 CAMPO GRANDE      MATTO GROSSO DO SUL COMPOSANTE VERTICALE BRESIL  
 20 27 49S      54 36 55W      H 450M P 0M D 1000KM  
 FORMATION SABLEUSE (ARENITO CAMA) 40M SUR EASALTE  
 DPT. DE HIDROLOGIA E TRANSPORTE - UNIV. FED. DE MATTO GROSSO DO SUE  
 CENTRO POLITECNICO-GEODESIA-U.F.PR.      PROF. C.GEMAEI  
 GRAVIMETRE LACOSTE ROMBERG 8      TRANS WORLD TIDAL GRAVITY PROFILES P.MELCHIOR  
 CALIBRATION      BRUXELLES - STATION FONDAMENTALE  
 INSTALLATION      C.POITEVIN, E.RATTON  
 MAINTENANCE      L.M.NUNES CARNEIRO, A.INACIO ARAUJO, JORGE GONDA

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING P.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ PRUSSELS  
 COMPUTER SPERRY-UNIVAC 110C/81      PROCESSED ON 85/ 3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .96620

PHASE LAG O1 1.366 M2 1.633 O1/M2 .836

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/O1 1.01912 /MODEL 2/

G 3 831113/831119 831125/831219 831229/84 124 24 129/84 131 84 2 6/84 2 6  
 G 8 84 310/84 312 84 4 7/84 4 9

TIME INTERVAL 150.0 DAYS      1824 READINGS      7 BLOCKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | PESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139.              | 30 31     | 5.00 .72                  | 1.2E51          | .1839  | -2.622         | 8.202  | .54              | 154.7  |
| 143.-149.              | 26 01     | 23.19 .68                 | 1.14C5          | .0335  | -1.114         | 1.676  | .59              | 49.4   |
| 161.-168.              | 33 P1S1K1 | 33.05 .57                 | 1.1559          | .0199  | -3.289         | .972   | 1.95             | 103.9  |
| 243.-248.              | 24 N2     | 14.30 .43                 | 1.1337          | .0339  | .633           | 1.733  | .37              | 154.6  |
| 252.-258.              | 26 M2     | 77.66 .40                 | 1.1792          | .0060  | 1.708          | .296   | 2.62             | 62.2   |
| 267.-277.              | 21 S2K2   | 36.29 .42                 | 1.1843          | .0137  | -1.437         | .671   | 1.17             | -51.2  |
| 335.-375.              | 16 M3     | 1.20 .22                  | .9925           | .1847  | -3.843         | 10.850 | .12              | -139.2 |
| STANDARD DEVIATION     | D         | 18.83                     | SD              | 9.85   | TD             | 5.72   | MICROGAL         |        |
| 01/K1                  | .9867     | 1-01/1-K1                 | .9014           | M2/01  | 1.0339         |        |                  |        |
| CENTRAL EPCCH TJJ=     | 2445726.0 |                           |                 |        |                |        |                  |        |

## TRANS WORLD PROFILE

## SOUTH AMERICA

## STATION VICOSA

STATION 7308 VICOSA MINAS GERAIS COMPOSANTE VERTICALE ERESIL  
 20 45 20S 42 52 04W H 650M P 0M D 400KM  
 DEPT. DE ENC. CIVIL - UNIV. FED. DE VICOSA PROF. A. S. FERRAZ  
 CENTRO POLITECNICO-GEODESIA-U.F.PR. PROF. C.GEMAEL  
 GRAVIMETRE LA COSTE ROMBERG 3 TRANS WORLD TIDAL GRAVITY PROFILES P.MELCHIOR  
 CALIBRATION BRUXELLES - STATION FONDAMENTALE  
 INSTALLATION C.POITEVIN,E.RATTON  
 MAINTENANCE A.S.FERRAZ,A.S.SILVA,J.GRIPP JR.

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/3/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .97410

PHASE LAG O1 1.350 M2 1.240 O1/M2 1.089

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/O1 1.01693 /MODEL 2/

|                   |               |               |               |               |
|-------------------|---------------|---------------|---------------|---------------|
| G 3 831030/831111 | 831115/831121 | 831127/8312 3 | 8312 8/831216 | 831221/84 110 |
| G 3 84 116/84 124 | 84 2 2/84 2 8 | 84 217/84 217 | 84 220/84 222 | 84 3 1/84 3 9 |
| G 3 84 313/84 317 | 84 322/84 322 | 84 326/84 4 1 | 84 411/84 411 |               |

TIME INTERVAL 166.5 DAYS 2736 READINGS 14 BLOKS

| WAVE GROUP<br>ARGUMENT | ESTIMATED AMPL.<br>R.WAVE | AMPL.<br>R.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|---------------------------|-----------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-136. 20 Q1        | 4.65                      | .30             | 1.1805          | .0771  | -4.812         | 3.700  | .40              | 99.7   |
| 143.-145. 16 O1        | 24.66                     | .31             | 1.1985          | .0150  | -2.547         | .722   | 1.35             | 125.5  |
| 152.-155. 15 N01       | 1.88                      | .27             | 1.1628          | .1679  | 4.383          | 8.193  | .14              | -90.4  |
| 161.-163. 10 P1        | 12.77                     | .29             | 1.3341          | .0307  | 1.058          | 1.316  | 1.74             | -172.2 |
| 164.-168. 23 S1K1      | 34.43                     | .30             | 1.1899          | .0103  | -2.565         | .501   | 2.14             | 133.8  |
| 175.-177. 14 J1        | 2.26                      | .30             | 1.3962          | .1838  | 8.578          | 7.523  | .49              | -136.5 |
| 184.-186. 11 001       | 1.28                      | .24             | 1.4440          | .2661  | -8.590         | 10.565 | .30              | 141.1  |
| 233.-23X. 20 2N2       | 2.21                      | .13             | 1.0995          | .0626  | 6.113          | 3.276  | .27              | 119.7  |
| 243.-248. 24 N2        | 15.40                     | .16             | 1.2261          | .0128  | 2.143          | .603   | 1.00             | 35.1   |
| 252.-258. 26 M2        | 78.44                     | .16             | 1.1956          | .0024  | 1.771          | .115   | 3.34             | 46.6   |
| 265.-265. 9 L2         | 2.13                      | .13             | 1.1472          | .0716  | 3.327          | 3.612  | .13              | 102.5  |
| 267.-273. 9 S2         | 37.02                     | .14             | 1.2129          | .0046  | 2.114          | .217   | 2.09             | 40.7   |
| 274.-277. 12 K2        | 10.15                     | .14             | 1.2224          | .0166  | .219           | .783   | .52              | 4.3    |
| 335.-375. 16 M3        | 1.28                      | .09             | 1.0665          | .0706  | -4.01          | 3.768  | .01              | -96.7  |

|                              |           |        |       |       |               |
|------------------------------|-----------|--------|-------|-------|---------------|
| STANDARD DEVIATION D         | 9.22      | SD     | 4.64  | TD    | 2.79 MICROGAL |
| 01/K1. 1.0072                | 1-01/1-K1 | 1.0451 | M2/01 | .9976 |               |
| CENTRAL EPOCH TJU= 2445720.0 |           |        |       |       |               |

TRANS WORLD PROFILE

SOUTH AMERICA

STATION CUIABA

STATION 7309 CUIABA MATTO GROSSO N COMPOSANTE VERTICALE BRESIL  
 15 36 33 S 56 07 34 W H 154 P 0M D 1882KM  
 PRECAMBRIAN, PHYLLITES AND QUARTZITES, LOW GRADE METAMORPHIC ROCK  
 UNIVERSIDADE FEDERAL DE MATTO GROSSO - DEPARTAMENTO DE GEOLOGIA  
 GRAVIMETRE GEODYNAMICS 783 P.MELCHIOR - OBSERVATOIRE ROYAL DE BELGIQUE  
 CALIBRATION BRUXELLES - FUNDAMENTAL STATION/NC50.4V/  
 INSTALLATION C.POITEVIN,E.RATTON  
 MAINTENANCE N.NAVEEN CHANDRA,K.J.ALBRECHT

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/3/13

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .95339

PHASE LAG O1 .415 M2 .844 O1/M2 .492

CORRECTION FOR ATTENUATION O1 1.00003 M2 1.00011 /MODEL 1/

G783 841128/841210 841214/841214 841218/841220 85 1 3/85 1 9 85 113/85 129

TIME INTERVAL 64.5 DAYS 1104 READINGS 5 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE       |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|-------------|
| 133.-139.              | 30 Q1     | 3.34                      | .14             | 1.0834 | .0465          | 2.551  | .482             | .28 -32.0   |
| 143.-149.              | 26 O1     | 18.63                     | .11             | 1.1581 | .0011          | .404   | .353             | .13 -81.2   |
| 161.-168.              | 33 P1S1K1 | 26.00                     | .09             | 1.1495 | .0041          | 2.294  | .203             | 1.07 -103.4 |

|           |         |       |     |        |       |       |      |           |
|-----------|---------|-------|-----|--------|-------|-------|------|-----------|
| 243.-248. | 24 N2   | 15.47 | .24 | 1.1614 | .0182 | 1.379 | .897 | .37 88.0  |
| 252.-258. | 26 M2   | 81.31 | .20 | 1.1685 | .0028 | 1.427 | .135 | 2.10 74.5 |
| 267.-277. | 21 S2K2 | 37.76 | .22 | 1.1663 | .0068 | 2.122 | .334 | 1.41 82.8 |

|           |       |      |     |        |       |       |       |          |
|-----------|-------|------|-----|--------|-------|-------|-------|----------|
| 335.-375. | 16 M3 | 1.46 | .04 | 1.1107 | .0337 | 3.767 | 1.744 | .11 60.7 |
|-----------|-------|------|-----|--------|-------|-------|-------|----------|

|                              |        |           |        |       |        |     |          |
|------------------------------|--------|-----------|--------|-------|--------|-----|----------|
| STANDARD DEVIATION           | O      | 2.49      | SD     | 3.61  | TD     | .87 | MICROGAL |
| 01/K1                        | 1.0075 | 1-01/1-K1 | 1.0574 | M2/01 | 1.0090 |     |          |
| CENTRAL EPOCH TJJ= 2446064.0 |        |           |        |       |        |     |          |

TRANS WORLD PROFILE

SOUTH AMERICA

STATION GOIANIA

STATION 7310 GOIANIA      GOIAS      COMPOSANTE VERTICALE      BRESIL  
 16 37 13 S    49 15 19W      H 764M      P 0M      D 875KM  
 GNAISSES DO COMPLEXO BASAL GOIANO(PRECAMBRIANO), LATOSOLO VERMELHO-AMARELADO  
 UNIVERSIDADE FEDERAL DE GOIAS - INSTITUTO DE QUIMICA E GEOCIENCIAS  
 GRAVIMETRE GEODYNAMICS 783      P.MELCHIOR - OBSERVATOIRE ROYAL DE BELGIQUE  
 CALIBRATION      BRUXELLES - FUNDAMENTAL STATION/NC50.4V/  
 INSTALLATION      C.POITEVIN,E.RATTON  
 MAINTENANCE      J.VANDERLIN,E.DE OLIVEIRA COSTA,J.E.ALBUQUERQUE

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81      PROCESSED ON 85/ 1/18

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR .95339

PHASE LAG O1 .415 M2 .844 O1/M2 .492

CORRECTION FOR ATTENUATION O1 1.00003 M2 1.00011 /MODEL 1/

|                    |               |               |               |               |
|--------------------|---------------|---------------|---------------|---------------|
| G783 84 5 4/84 6 1 | 84 6 5/84 621 | 84 628/84 7 2 | 84 7 5/84 7 7 | 84 712/84 716 |
| G783 84 8 7/8410 4 | 8410 9/841017 | 841024/841113 | 841117/841117 |               |

TIME INTERVAL 199.0 DAYS      3792 READINGS      9 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|--------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-136. 20 Q1        |        | 4.04 .09                  | 1.2395          | .0280  | -.176          | 1.291  | .26              | 177.3  |
| 143.-145. 16 O1        |        | 19.75 .09                 | 1.1607          | .0055  | -.622          | .271   | .22              | 96.2   |
| 152.-155. 15 N01       |        | 1.51 .07                  | 1.1279          | .0492  | 4.748          | 2.491  | .13              | -69.7  |
| 161.-163. 10 P1        |        | 9.15 .10                  | 1.1561          | .0128  | .461           | .631   | .08              | -104.6 |
| 164.-168. 23 S1K1      |        | 27.51 .09                 | 1.1498          | .0039  | -1.703         | .193   | .86              | 108.9  |
| 175.-177. 14 J1        |        | 1.72 .09                  | 1.2876          | .0654  | -1.285         | 2.894  | .17              | 167.1  |
| 184.-186. 11 001       |        | .75 .07                   | 1.0239          | .0896  | -5.245         | 4.999  | .12              | 33.6   |
| 233.-23X. 20 2N2       |        | 2.32 .07                  | 1.1024          | .0317  | 1.654          | 1.641  | .14              | 151.3  |
| 243.-248. 24 N2        |        | 15.57 .08                 | 1.1802          | .0063  | 2.441          | .306   | .71              | 69.2   |
| 252.-258. 26 M2        |        | 80.67 .08                 | 1.1711          | .0012  | 1.862          | .059   | 2.72             | 74.6   |
| 265.-265. 9 L2         |        | 2.32 .10                  | 1.1928          | .0491  | 4.634          | 2.350  | .20              | 73.4   |
| 267.-273. 9 S2         |        | 37.66 .08                 | 1.1751          | .0026  | 1.511          | .126   | 1.10             | 64.5   |
| 274.-277. 12 K2        |        | 10.08 .07                 | 1.1556          | .0082  | 1.681          | .406   | .30              | 98.3   |
| 335.-375. 16 M3        |        | 1.43 .02                  | 1.1071          | .0186  | 2.031          | .958   | .07              | 45.1   |

|                              |        |           |        |       |        |              |
|------------------------------|--------|-----------|--------|-------|--------|--------------|
| STANDARD DEVIATION           | D      | 3.72      | SD     | 3.13  | TC     | .29 MICROGAL |
| 01/K1                        | 1.0095 | 1-01/1-K1 | 1.0730 | M2/01 | 1.0089 |              |
| CENTRAL EPOCH TJJ= 2445923.0 |        |           |        |       |        |              |



TRANS WORLD PROFILE  
STATION 7505 SANTA CRUZ

SOUTH AMERICA  
COMPOSANTE VERTICALE

STATION SANTA CRUZ  
BOLIVIE

17 46 30 S 63 11 33 W H 410M P DM D 700KM  
SEDIMENTS QUATERNAIRES ALLUVIAUX DU RIO PIRAI, MELANGE SABLE ET ARGILE  
CENTRO NACIONAL DE ENFERMEDADES TROPICALES DEL MINISTERIO DE PREVISION SOCIAL  
GRAVIMETRE GEODYNAMICS 084 P.MELCHIOR - OBSERVATOIRE ROYAL DE BELGIQUE  
UNITE DE CONTROLE RENOVEE - M.VAN RUYMBEKE  
CALIBRATION BRUXELLES - FUNDAMENTAL STATION/50.05V/  
INSTALLATION M.VAN RUYMBEKE  
MAINTENANCE CH.DARRAS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 84/10/31

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR 1.17288

PHASE LAG O1 .692 M2 .913 O1/M2 .758  
CORRECTION FOR DIFFERENTIAL ATTENUATION M2/O1 1.00968 /MODEL 2/

G 64 84 6 5/84 825 84 828/84 913 84 926/84 926

TIME INTERVAL 54.0 DAYS 1008 READINGS 3 BLOKS

| WAVE GROUP<br>ARGUMENT       | N  | WAVE   | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S.        | RESIDUE<br>AMPL. | PHASE |        |
|------------------------------|----|--------|---------------------------|-----------------|--------|----------------|---------------|------------------|-------|--------|
| 133.-139.                    | 30 | Q1     | 3.97                      | .13             | 1.1501 | .0368          | .577          | 1.803            | .05   | -50.8  |
| 143.-149.                    | 26 | O1     | 20.89                     | .14             | 1.1575 | .0078          | 1.103         | .381             | .40   | -84.9  |
| 161.-168.                    | 33 | P1S1K1 | 29.58                     | .15             | 1.1656 | .0061          | -1.394        | .301             | 1.00  | 134.3  |
| 243.-248.                    | 24 | N2     | 15.68                     | .14             | 1.2042 | .0105          | 1.247         | .508             | .66   | 30.9   |
| 252.-258.                    | 26 | M2     | 81.01                     | .15             | 1.1909 | .0022          | .857          | .106             | 2.41  | 30.1   |
| 267.-277.                    | 21 | S2K2   | 37.98                     | .13             | 1.2000 | .0041          | 1.407         | .199             | 1.56  | 36.7   |
| 335.-375.                    | 16 | M3     | 1.26                      | .06             | .9877  | .0495          | -2.542        | 2.928            | .12   | -151.5 |
| STANDARD DEVIATION           |    | D      | 2.77                      | SD              | 2.71   | TD             | 1.20 MICROGAL |                  |       |        |
| O1/K1                        |    | .9931  | 1-01/1-K1                 | .9514           | M2/01  | 1.0288         |               |                  |       |        |
| CENTRAL EPOCH TJJ= 2445943.C |    |        |                           |                 |        |                |               |                  |       |        |

TRANS WORLD PROFILES  
STATION 3321 LAMTO

WEST AFRICA  
COMPOSANTE VERTICALE

STATION ABIDJAN/LAMTO  
COTE D'IVOIRE

6 13 28N 05 01 40W H 101M P 4M D 120KM

GRANITO GNEISS ET GRANITE

OBSERVATOIRE GEOPHYSIQUE DE LAMTO-J.L. TOURNIER.

GRAVIMETRE GEODYNAMICS 765 OBSERVATOIRE ROYAL DE BELGIQUE-P. MELCHIOR

CALIBRATION BRUXELLES STATION FONDAMENTALE /LWA49.78V/

INSTALLATION M. VAN RUYMBEKE

MAINTENANCE J.L. TIREFORD

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 84/ 9/ 5

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

NORMALISATION FACTOR 1.20032

PHASE LAG 01 .406 M2 .802 01/M2 .506

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/01 1.00279 /MODEL 2/

5765 84 126/84 2 5 84 2 9/84 219 84 225/84 515 84 519/84 6 4 84 6 8/84 618

TIME INTERVAL 145.5 DAYS 3264 READINGS 5 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>P.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | PESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139. 30 Q1        |           | 1.61 .08                  | 1.2594          | .3619  | 1.935          | 2.811  | .14              | 23.2   |
| 143.-149. 26 01        |           | 7.89 .08                  | 1.1797          | .0116  | -1.688         | .564   | .27              | -60.2  |
| 161.-168. 33 P1S1K1    |           | 9.85 .08                  | 1.0470          | .0085  | -2.630         | .468   | .97              | -152.4 |
| 243.-248. 24 N2        |           | 16.86 .26                 | 1.1880          | .0180  | 4.025          | .863   | 1.24             | 73.3   |
| 252.-258. 26 M2        |           | 87.99 .26                 | 1.1872          | .0035  | 1.944          | .170   | 3.57             | 56.7   |
| 267.-277. 21 S2K2      |           | 41.15 .23                 | 1.1935          | .0065  | 1.444          | .318   | 1.54             | 42.3   |
| 335.-375. 16 M3        |           | 1.56 .02                  | 1.0806          | .0135  | 1.864          | .711   | .05              | 70.2   |
| STANDARD DEVIATION     | D         | 3.00                      | SD              | 9.19   | TD             | .67    | MICROGAL         |        |
| 01/K1 1.1268           | 1-01/1-K1 | 3.8261                    | M2/01           | 1.0064 |                |        |                  |        |
| CENTRAL EPOCH          | TJJ=      | 2445798.0                 |                 |        |                |        |                  |        |

**TRANS WORLD PROFILES  
STATION 3400 NIAMEY**

## WEST AFRICA COMPOSANTE VERTICALE

STATION NIAMEY  
NIGER

13 30 56.6 N 02 06 15.3 E H 200 M P CM D 810KM  
SEDIMENTS, FORMATIONS SABLEUSES EN TERRASSES  
SERVICE TOPOGRAPHIQUE BP 250 NIAMEY  
GRAVIMETRE LA COSTE-ROMBERG 336, ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMBEKE,  
AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
CALIBRATION BRUXELLES STATION FONDAMENTALE  
INSTALLATION M. VAN RUYMBEKE  
MAINTENANCE J.E. MARCHE, MAMANE WAZIRI, MAMANE HALIDOU

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED CN 84/ 9/ 4

**INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR .99571**

TIME INTERVAL 133.0 DAYS 2208 READINGS 16 BLOKS

| WAVE GROUP<br>ARGUMENT | ESTIMATED AMPL.<br>N WAVE | AMPL.<br>R.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. PHASE |
|------------------------|---------------------------|-----------------|-----------------|--------|----------------|--------|------------------------|
| 133.-139. 30 Q1        | 2.86                      | .19             | 1.0585          | .0702  | -1.130         | 3.797  | .28 -168.3             |
| 143.-149. 26 01        | 16.37                     | .19             | 1.1608          | .0137  | -1.612         | .674   | .46 -88.2              |
| 161.-168. 33 P1S1K1    | 21.59                     | .20             | 1.0887          | .0101  | 1.394          | .535   | 1.11 151.7             |
| 243.-248. 24 N2        | 15.68                     | .10             | 1.1548          | .0071  | .253           | .352   | .10 136.4              |
| 252.-258. 26 M2        | 82.14                     | .10             | 1.1583          | .0014  | .809           | .071   | 1.17 96.5              |
| 267.-277. 21 S2K2      | 38.23                     | .09             | 1.1589          | .0026  | .835           | .129   | .56 94.5               |
| 335.-375. 16 M3        | 1.40                      | .06             | 1.0345          | .0422  | 3.216          | 2.297  | .09 120.7              |
| STANDARD DEVIATION     | D                         | 6.01            | SD              | 2.89   | TD             | 1.65   | MICROGAL               |
| 01/K1                  | 1.0662                    | 1-01/1-K1       | 1.8117          | M2/01  | .9979          |        |                        |
| CENTRAL EPOCH TJJE     | 2445791.0                 |                 |                 |        |                |        |                        |

TRANS WCRLD PROFILES  
STATION 3399 ARLIT

WEST AFRICA  
COMPOSANTE VERTICALE

STATION ARLIT  
NIGER

16 50 18 N 7 19 26 E H 418M P 0M D 1300KM

AMIDAP - STAFF TECHNIQUE

GRAVIMETRE LA COSTE-ROMBERG 336, ASSERVISSEMENT ELECTRONIQUE M. VAN RUYMBEKE,  
AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON

CALIBRATION BRUXELLES STATION FONDAMENTALE

INSTALLATION M. VAN RUYMBEKE

MAINTENANCE TH. DAGUENET, PH. MUYS, J.L. COLDERS

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT

COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS

COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 2/21

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR .99571

G336 84 616/84 616 84 624/84 7 2 84 720/84 724 84 728/84 8 1 84 8 9/84 817  
G336 24 621/84 621 84 825/84 829 84 9 4/84 9 8 84 920/84 930 8410 6/841014  
G336 841022/841030

TIME INTERVAL 138.0 DAYS 1920 READINGS 11 BLOKS

| WAVE GROUP<br>ARGUMENT       | N WAVE | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------------|--------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139. 30 Q1              |        | 4.43 .40                  | 1.2212          | .1106  | 3.853          | 5.161  | .37              | 54.3   |
| 143.-149. 26 O1              |        | 21.14 .41                 | 1.1149          | .0217  | -2.759         | 1.119  | 1.34             | -130.4 |
| 161.-168. 33 P1S1K1          | 30.61  | .43                       | 1.1477          | .0160  | 2.182          | .801   | 1.19             | 78.0   |
| 243.-248. 24 N2              |        | 14.60 .16                 | 1.1350          | .0124  | 2.036          | .634   | .62              | 122.6  |
| 252.-258. 26 M2              |        | 77.24 .17                 | 1.1493          | .0026  | .510           | .127   | 1.00             | 136.6  |
| 267.-277. 21 S2K2            |        | 35.94 .15                 | 1.1494          | .0049  | -.014          | .244   | .34              | -178.6 |
| 335.-375. 16 M3              |        | 1.59 .12                  | 1.2736          | .0955  | -2.980         | 4.277  | .27              | -17.9  |
| STANDARD DEVIATION           | D      | 11.94                     | SD              | 4.33   | TD             | 3.31   | MICROGAL         |        |
| 01/K1                        | .9714  | 1-01/1-K1                 | .7775           | M2/01  | 1.0309         |        |                  |        |
| CENTRAL EPOCH TJJ= 2445936.0 |        |                           |                 |        |                |        |                  |        |

TRANS WORLD PROFILES  
STATION 3325 OUAGADOUGOU

WEST AFRICA  
COMPOSANTE VERTICALE

STATION OUAGADOUGOU  
BOURKINA FASSO/HTE VOLTA

12 24 10 N 1 29 40 W H 290 M P 0M D 800KM  
SOCLE ARCHEEN ANTECAMBRIEN GRANITIQUE RECOUVERT DE 30M D'ALTERITE

CRTO - DIRECTEUR J.P.OUEDRAOGO

GRAVIMETRE GEODYNAMICS 765 OBSERVATOIRE ROYAL DE BELGIQUE-P.MELCHIOR  
CALIBRATION BRUXELLES STATION FONDAMENTALE /LWA49.78V/  
INSTALLATION M. VAN RUYMBEKE  
MAINTENANCE Y.KOUSOUBE, D.DAMASCO, F.RANTRUA, J.PARNOT

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EUDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 1/24

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR 1.20032

PHASE LAG .01 .406 M2 .802 01/M2 .506

CORRECTION FOR DIFFERENTIAL ATTENUATION M2/01 1.00279 /MODEL 2/

G765 84 7 7/84 7 7 84 710/84 714 84 720/84 910 84 915/84 929 8410 3/8410 7  
G765 841011/841013 841019/841029 8411 2/8411 4 841116/841116 841120/841124

TIME INTERVAL 142.5 DAYS 2688 READINGS 10 BLOKS

| WAVE GROUP<br>ARGUMENT       | N  | WAVE   | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S.        | RESIDUE<br>AMPL. | PHASE  |
|------------------------------|----|--------|---------------------------|-----------------|--------|----------------|---------------|------------------|--------|
| 133.-139.                    | 30 | Q1     | 2.58 .45                  | 1.1538          | .1786  | 11.395         | 6.871         | .57              | 97.1   |
| 143.-149.                    | 26 | 01     | 14.71 .47                 | 1.1302          | .0363  | -2.058         | 1.829         | .66              | -126.3 |
| 161.-168.                    | 33 | P1S1K1 | 22.48 .49                 | 1.2276          | .0268  | -3.467         | 1.261         | 2.11             | -40.2  |
| 243.-248.                    | 24 | N2     | 15.77 .19                 | 1.1515          | .0137  | 1.572          | .663          | .45              | 106.0  |
| 252.-258.                    | 26 | M2     | 81.72 .20                 | 1.1422          | .0028  | 1.253          | .140          | 2.21             | 126.1  |
| 267.-277.                    | 21 | S2K2   | 38.27 .17                 | 1.1497          | .0051  | 1.279          | .259          | .93              | 112.7  |
| 335.-375.                    | 16 | M3     | 1.33 .05                  | .9720           | .0362  | .611           | 2.133         | .13              | 173.8  |
| STANDARD DEVIATION           |    |        | D 16.11                   | SD              | 6.15   | TD             | 1.62 MICROGAL |                  |        |
| 01/K1 .9205 1-01/1-K1 .5714  |    |        | M2/01                     | 1.0106          |        |                |               |                  |        |
| CENTRAL EPOCH TJJ= 2445959.0 |    |        |                           |                 |        |                |               |                  |        |

NORTH-SOUTH EUROPEAN PROFILE  
STATION 0886 KEVO

COMPOSANTE VERTICALE

STATION KEVO  
FINLANDE

69 45 22 N 27 07 37 E H 99 M P 1 M D 70KM

KEVO SUBARCTIC RESEARCH STATION

UTSJOKI - SURF.BUILD. OLD CONCRETE PILLAR ON BEDROCK, MIGMATITE 2.71  
GEODEETTIEN LAITOS HELSINKI J.KAKKURI

GNEISSE GRANITE

OBSERVATOIRE ROYAL DE FELGIQUE DEPT.1 P.MELCHIOR  
GRAVIMETRE LA COSTE-ROMBERG 402, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
CALIBRATION LA COSTE - ROMBERG  
INSTALLATION B.DUCARME, J.KAARIAINEN  
MAINTENANCE I.NURMINEN

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-LILLEY / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 84/10/5

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

6402 64 4 2/84 412 84 420/84 5 6 84 510/84 522 84 526/84 6 5 84 6 9/84 8 2  
6402 84 8 2/84 626 84 830/84 911

TIME INTERVAL 164.5 DAYS 1504 READINGS 7 BLOKS

| WAVE GROUP         | ESTIMATED AMPL. |           | PHASE  | RESIDUE |        |              |
|--------------------|-----------------|-----------|--------|---------|--------|--------------|
| ARGUMENT           | N WAVE          | R.M.S.    | FACTOR | R.M.S.  | AMPL.  | PHASE        |
| 133.-136.          | 20 Q1           | 4.32      | .11    | 1.1161  | .0279  | 1.195        |
| 143.-145.          | 16 01           | 23.32     | .10    | 1.1540  | .0051  | .554         |
| 152.-155.          | 15 N01          | 1.86      | .08    | 1.1689  | .0513  | 2.252        |
| 161.-163.          | 10 P1           | 11.09     | .12    | 1.1789  | .0126  | .874         |
| 164.-168.          | 23 S1K1         | 32.67     | .11    | 1.1499  | .0038  | -.878        |
| 175.-177.          | 14 J1           | 1.73      | .10    | 1.0860  | .0634  | -3.569       |
| 184.-186.          | 11 001          | 1.00      | .08    | 1.1516  | .0900  | -2.610       |
| 233.-23X.          | 20 2N2          | .29       | .03    | 1.0489  | .0977  | 4.141        |
| 243.-248.          | 24 N2           | 1.98      | .03    | 1.1493  | .0172  | 7.267        |
| 252.-258.          | 26 M2           | 11.10     | .03    | 1.2325  | .0033  | 5.859        |
| 265.-265.          | 9 L2            | .33       | .04    | 1.3010  | .1620  | 21.399       |
| 267.-273.          | 9 S2            | 5.19      | .03    | 1.2389  | .0071  | 1.537        |
| 274.-277.          | 12 K2           | 1.39      | .03    | 1.2157  | .0229  | 3.504        |
| 335.-375.          | 16 M3           | .08       | .01    | 1.2861  | .1625  | 1.800        |
| STANDARD DEVIATION | D               | 4.006     | SD     | 1.06    | TD     | .35 MICROGAL |
| 01/K1              | 1.0036          | 1-01/1-K1 | 1.0271 | M2/01   | 1.0680 |              |
| CENTRAL EPOCH      | TJJ=            | 2445874.0 |        |         |        |              |

NORTH-SOUTH EUROPEAN PROFILE  
STATION 0886 KEVO

## **COMPOSANTE VERTICALE**

STATION KEVO  
FINLANDE

69 45 22 N 27 07 37 E H 99 M . P I M D 70KM

# KERO SUBAPCTIC RESEARCH STATION

UTSJOKI - SURF. BUILT. OLD CONCRETE PILLAR ON BEDROCK. MIGMATITE 2.71

GEOODEETTINEN LAITOS HELSINKI J. KAKKUPI

GNEISSE GRANITE

CATEDRA DE ASTRONOMIA Y GEODESIA. UNIVERSIDAD COMPLUTENSE MADRID. J. M. TORROJA

GRAVIMETRE LA COSTE-POMEYRC 665. ASSERVISSEMENT ELECTRONIQUE N.VAN RHYMBEKE.

#### AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON

## ADMISSION CALTEPATION

**CALEY AVIATION  
INSTALLATION** **LA COSTE - FONBERG  
B. BUGAUME L. KAARTA**

**INSTALLATION** E. DUCLARME, J. PAAJIAIHNEN  
**M A I N T E N A N C E** H. NURMINEN

## MAINTENANCE

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLOR-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/61 PROCESSED ON ES/ 3/20

**INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR 1.00729**

3665 84 4 4/84 414 84 417/84 720 84 724/84 8 5 84 8 9/84 827 84 831/84 914

TIME INTERVAL 165.5 DAYS 3792 READINGS  $\pm$  BLOCKS

STATION 0402 MADRID

COMPOSANTE VERTICALE

ESPAGNE

40 27 07 N 03 43 28 E H 650 M P O M D 320KM  
 GRAVIMETRE LA COSTE-ROMBERG 402, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION LA COSTE - ROMBERG.  
 INSTALLATION  
 MAINTENANCE

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 2/15

INEPTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

G402 E4 930/841030 8411 3/8412 5

TIME INTERVAL 68.0 DAYS 1584 READINGS 2 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | PESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139.              | 30 Q1     | 6.87 .08                  | 1.1689          | .0142  | -.829          | .697   | .11              | -61.3  |
| 143.-149.              | 26 01     | 35.26 .09                 | 1.1491          | .0029  | -.376          | .142   | .39              | -143.6 |
| 161.-168.              | 33 P1S1K1 | 46.95 .09                 | 1.1345          | .0021  | .475           | .104   | .43              | 108.4  |
| 243.-248.              | 24 N2     | 9.20 .08                  | 1.1052          | .0097  | 3.951          | .502   | .79              | 127.1  |
| 252.-258.              | 26 M2     | 49.81 .08                 | 1.1454          | .0019  | 4.642          | .096   | 4.11             | 101.2  |
| 267.-277.              | 21 S2K2   | 23.91 .07                 | 1.1818          | .0034  | 3.344          | .167   | 1.45             | 74.1   |
| 335.-375.              | 16 M3     | .67 .03                   | 1.0257          | .0521  | -3.222         | 2.904  | .05              | -126.9 |

STANDARD DEVIATION D 2.38 SD 2.03 TD .81 MICROGAL  
 01/K1 1.0129 1-01/1-K1 1.1085 M2/01 .9968  
 CENTRAL EPOCH TJJ= 2446007.0

STATION 0402 MADRID

COMPOSANTE VERTICALE

ESPAGNE

40 27 07 N 03 43 28 E H 650 M P O M D 320KM  
 GRAVIMETRE LA COSTE-ROMBERG 487, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION LA COSTE - ROMBERG  
 INSTALLATION R. VIEIRA  
 MAINTENANCE F. VIEIRA

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-ELDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 25/ 2/19

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

G487 841C11/841011 841014/841016 841C20/841030 8411 5/841119 841123/841125  
 G487 841129/8412 3

TIME INTERVAL 55.5 DAYS 1056 READINGS 6 BLOKS

| WAVE GROUP<br>ARGUMENT       | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOP | R.M.S.   | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. PHASE |
|------------------------------|-----------|---------------------------|-----------------|----------|----------------|--------|------------------------|
| 133.-139.                    | 30 Q1     | 6.62 .16                  | 1.1270          | .0264    | -3.090         | 1.340  | .41 -119.4             |
| 143.-149.                    | 26 01     | 35.16 .16                 | 1.1458          | .0051    | -.360          | .253   | .47 -151.9             |
| 161.-168.                    | 33 P1S1K1 | 49.14 .15                 | 1.1389          | .0035    | .019           | .177   | .06 15.6               |
| 243.-248.                    | 24 N2     | 9.27 .08                  | 1.1138          | .0100    | 4.324          | .505   | .81 120.5              |
| 252.-258.                    | 26 M2     | 49.75 .08                 | 1.1439          | .0019    | 4.264          | .097   | 3.79 102.8             |
| 267.-277.                    | 21 S2K2   | 23.78 .07                 | 1.1754          | .0035    | 3.268          | .175   | 1.38 78.7              |
| 335.-375.                    | 16 M3     | .66 .06                   | 1.0216          | .0935    | -9.217         | 5.264  | .11 -109.8             |
| STANDARD DEVIATION<br>01/K1  | D 1.0061  | SD 1-01/1-K1              | M2/01 1.0496    | TD .9983 |                |        | 1.23 MICROGAL          |
| CENTRAL EPOCH TJJ= 2446011.0 |           |                           |                 |          |                |        |                        |

## TRANS EUROPEAN PROFILE

## STATION B: IXELLES

STATION 0201 BRUXELLES-UCCLE      COMPOSANTE VERTICALE      BELGIQUE  
 50 47 55 N 04 21 29 E H 101 M P 4M C 90KM 981 117 301  
 BASSIN EOCENE DE BRUXELLES SUR LE CAMBRIEN DU MASSIF DU BRABANT.  
 SABLES LUTETIENS.

OBSERVATOIRE ROYAL DE BELGIQUE      DEPT.1 P.MELCHIOR  
 GRAVIMETRE LA COSTE-ROMBERG 402, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION                            LA COSTE - ROMBERG  
 INSTALLATION                        M. VAN RUYMBEKE  
 MAINTENANCE                        R. LAURENT, J. JEAN

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTEP INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 84/ 5/ 7

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

6402 64 1 3/84 1 9 84 115/84 121 84 125/84 2 6 84 211/84 318

TIME INTERVAL 77.0 DAYS 1632 READINGS 4 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>P.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139. 30 Q1        |           | 6.85 .09                  | 1.1746          | .0163  | -1.108         | .791   | .16              | -56.8  |
| 143.-149. 26 01        |           | 35.32 .11                 | 1.1599          | .0036  | .185           | .179   | .12              | 81.6   |
| 161.-168. 33 P1S1K1    | 49.06     | .11                       | 1.1456          | .0025  | .185           | .126   | .38              | 25.0   |
| 243.-248. 24 N2        |           | 6.75 .05                  | 1.1741          | .0086  | 3.309          | .418   | .40              | 80.0   |
| 252.-258. 26 M2        |           | 35.55 .06                 | 1.1842          | .0019  | 2.732          | .093   | 1.83             | 66.0   |
| 267.-277. 21 S2K2      |           | 16.81 .05                 | 1.2036          | .0037  | 1.435          | .178   | .74              | 34.9   |
| 335.-375. 16 M3        |           | .37 .03                   | .9946           | .0689  | -4.975         | 3.939  | .04              | -131.6 |
| STANDARD DEVIATION     | D         | 2.85                      | SD              | 1.42   | TD             | .64    | MICROGAL         |        |
| 01/K1 1.0125           | 1-01/1-K1 | 1.0983                    | M2/01           | 1.0210 |                |        |                  |        |
| CENTRAL EPOCH          | TJJ=      | 2445740.0                 |                 |        |                |        |                  |        |

## TRANS WORLD PROFILES

## BRUSSELS FUNDAMENTAL STATION

STATION 0201 BRUXELLES-UCCLE      COMPOSANTE VERTICALE      BELGIQUE  
 50 47 55 N    04 21 29 E    H 101 M P 4M D 90KM 981 117 301  
 BASSIN EOCENE DE BRUXELLES SUR LE CAMBRIEN DU MASSIF DU BRABANT.  
 SABLES LUTETIENS.  
 OBSERVATOIRE ROYAL DE BELGIQUE      DEPT.1      P.MELCHIOR  
 GRAVIMETRE LA COSTE-ROMBERG 336, ASSEZVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION      LA COSTE - ROMBERG  
 INSTALLATION      M. VAN RUYMBEKE  
 MAINTENANCE      P. LAURENT, J. JEAN

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81      PROCESSED ON 84/ 5/10

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR .99571

G336 831020/831028 8311 1/831113 831117/831129 8312 2/8312 8 831212/831220  
 G336 831224/831228 84 1 1/84 111

TIME INTERVAL 85.0 DAYS 1776 READINGS 7 BLOKS

| WAVE GROUP<br>ARGUMENT       | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE    |        |
|------------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|----------|--------|
| 133.-139.                    | 30 Q1     | 6.65                      | .10             | 1.1403 | .0167          | .275   | .237             | .12      | 164.1  |
| 143.-149.                    | 26 01     | 35.36                     | .08             | 1.1610 | .0028          | -.034  | .137             | .06      | -22.0  |
| 161.-168.                    | 33 P1S1K1 | 49.30                     | .07             | 1.1510 | .0017          | .359   | .086             | .65      | 28.1   |
| 243.-248.                    | 24 N2     | 6.75                      | .05             | 1.1746 | .0079          | 2.414  | .384             | .29      | 74.2   |
| 252.-258.                    | 26 M2     | 35.61                     | .04             | 1.1928 | .0014          | 2.618  | .067             | 1.89     | 60.2   |
| 267.-277.                    | 21 S2K2   | 16.89                     | .04             | 1.2094 | .0030          | 1.206  | .143             | .77      | 27.4   |
| 335.-375.                    | 16 M3     | .37                       | .02             | .9877  | .0564          | -3.837 | 3.250            | .04      | -141.1 |
| STANDARD DEVIATION           |           | D                         | 2.34            | SD     | 1.06           | TD     | .54              | MICROGAL |        |
| 01/K1                        |           | 1.0087                    | 1-01/1-K1       | 1.0662 | M2/01          | 1.0273 |                  |          |        |
| CENTRAL EPOCH TJJ= 2445669.0 |           |                           |                 |        |                |        |                  |          |        |

## TRANS EUROPEAN PROFILE

## STATION BRUXELLES

STATION 0201 BRUXELLES-UCCLE      COMPOSANTE VERTICALE      BELGIQUE  
 50 47 55 N    04 21 29 E    H 101 M P 4M D 90KM 981 117 301  
 BASSIN EOCENE DE BRUXELLES SUR LE CAMBRIEN DU MASSIF DU BRABANT.  
 SABLES LUTETIENS.  
 OBSERVATOIRE ROYAL DE BELGIQUE      DEPT.1      P.MELCHIOR  
 INSTITUTO DI ASTRONOMIA Y GEODESIA DEL C.N.R., UNIV.COMPLUTENSE MADRID, R.VIEIRA  
 GRAVIMETRE LA COSTE-ROMBERG 434, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION      LA COSTE - ROMBERG  
 INSTALLATION      B.DUCARME  
 MAINTENANCE      R. LAURENT, J. JEAN, ZHOU KUNGEN

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 1100/81      PROCESSED ON 85/2/25

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR 1.02111

G434 6412 5/85 122 85 130/85 2 7 85 211/85 211 85 215/85 215

TIME INTERVAL 74.0 DAYS 1536 READINGS 4 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE  |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|--------|
| 133.-139. 30 Q1        |           | 6.73 .12                  | 1.1546          | .0214  | -.087          | 1.063  | .03              | -160.3 |
| 143.-149. 26 01        |           | 35.36 .10                 | 1.1610          | .0034  | -.138          | .169   | .10              | -58.1  |
| 161.-168. 33 P1S1K1    | 49.34 .09 |                           | 1.1520          | .0020  | .108           | .102   | .62              | 8.6    |
| 243.-248. 24 N2        |           | 6.70 .06                  | 1.1654          | .0112  | 3.160          | .552   | .37              | 86.9   |
| 252.-258. 26 M2        |           | 35.76 .05                 | 1.1913          | .0018  | 2.427          | .066   | 1.76             | 59.1   |
| 267.-277. 21 S2K2      |           | 16.91 .06                 | 1.2109          | .0043  | 1.147          | .208   | .78              | 25.6   |
| 335.-375. 16 M3        |           | .42 .02                   | 1.1234          | .0655  | 9.515          | 3.312  | .07              | 77.7   |
| STANDARD DEVIATION     | D         | 2.75                      | SD              | 1.25   | TD             | .58    | MICROGAL         |        |
| 01/K1 1.0078           | 1-01/1-K1 | 1.0593                    | M2/01           | 1.0261 |                |        |                  |        |
| CENTRAL EPOCH          | TJJ=      | 2446075.0                 |                 |        |                |        |                  |        |

?

## TRANS WORLD PROFILES

## BRUSSELS FUNDAMENTAL STATION

STATION 0201 BRUXELLES-UCCLE      COMPOSANTE VERTICALE      BELGIQUE  
 50 47 55 N    04 21 29 E    H 101 M P 4M D 90KM 981 117 301  
 BASSIN EOCENE DE BRUXELLES SUR LE CAMBRIEN DU MASSIF DU BRABANT.  
 SABLES LUTETIENS.

OBSERVATOIRE ROYAL DE BELGIQUE      DEPT.1 P.MELCHIOR  
 GRAVIMETRE LACOSTE ROMBERG 487, ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
 AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON  
 CALIBRATION      BRUXELLES - STATION FONDAMENTALE  
 INSTALLATION      M.VAN RUYMBEKE  
 MAINTENANCE      M.VAN RUYMBEKE-B.DUCARME-J.JEAN-R.LAURENT

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING P.DUCARME  
 POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
 COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
 COMPUTER SPERRY-UNIVAC 110C/61 PROCESSED ON 84/ 9/26

INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
 NORMALISATION FACTOR 1.01326

|      |           |     |           |     |           |     |           |     |           |     |
|------|-----------|-----|-----------|-----|-----------|-----|-----------|-----|-----------|-----|
| G487 | 84 331/84 | 4 2 | 84 515/84 | 523 | 84 527/84 | 531 | 84 6 3/84 | 611 | 84 619/84 | 623 |
| G467 | 84 622/84 | 630 | 84 7 4/84 | 7 4 | 84 714/84 | 714 | 84 717/84 | 8 4 | 84 8 9/84 | 817 |
| G487 | 84 821/84 | 823 |           |     |           |     |           |     |           |     |

TIME INTERVAL 147.5 DAYS      1872 READINGS      11 BLOKS

| WAVE GROUP<br>ARGUMENT | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | P.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE |
|------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|-------|
| 133.-139.              | 30 Q1     | 6.55 .14                  | 1.1236          | .0232  | .408           | 1.187  | .21              | 167.4 |
| 143.-149.              | 26 01     | 35.35 .13                 | 1.1610          | .0042  | .228           | .207   | .15              | 70.2  |
| 161.-168.              | 33 P1S1K1 | 49.50 .11                 | 1.1557          | .0026  | .163           | .132   | .79              | 10.3  |
| 243.-248.              | 24 N2     | 6.75 .06                  | 1.1749          | .0112  | 3.857          | .548   | .46              | 81.3  |
| 252.-258.              | 26 M2     | 35.78 .06                 | 1.1920          | .0021  | 2.519          | .100   | 1.82             | 59.6  |
| 267.-277.              | 21 S2K2   | 16.95 .07                 | 1.2138          | .0048  | 1.344          | .229   | .85              | 28.1  |
| 335.-375.              | 16 M3     | .42 .04                   | 1.1164          | .0959  | -.742          | 4.881  | .02              | -16.4 |

|                              |        |           |        |       |        |              |
|------------------------------|--------|-----------|--------|-------|--------|--------------|
| STANDARD DEVIATION           | D      | 3.54      | SD     | 1.57  | TD     | .93 MICROGAL |
| 0.1/K1                       | 1.0045 | 1-01/1-K1 | 1.0336 | M2/01 | 1.0267 |              |
| CENTRAL EPOCH TJJ= 2445863.0 |        |           |        |       |        |              |

## TRANS EUROPEAN PROFILE

## STATION BRUXELLES

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 85/ 2/14

## INEPTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS

G665 84 929/8410 1 8410 5/8410 7 841011/841017 841021/841023 841027/841029  
 G665 8411 2/8411 4 8411 8/841116 841122/841128

TIME INTERVAL 62.0 DAYS 1152 READINGS 8 BLOKS

| WAVE GROUP<br>ARGUMENT         | N WAVE    | ESTIMATED AMPL.<br>R.M.S. | AMPL.<br>FACTOR | R.M.S. | PHASE<br>DIFF. | R.M.S. | RESIDUE<br>AMPL. | PHASE    |        |
|--------------------------------|-----------|---------------------------|-----------------|--------|----------------|--------|------------------|----------|--------|
| 133.-139.                      | 30 Q1     | 6.78                      | .12             | 1.1636 | .0208          | -810   | 14009            | .10      | -76.5  |
| 143.-149.                      | 26 01     | 35.40                     | .13             | 1.1624 | .0042          | 013    | .203             | .09      | 4.7    |
| 161.-168.                      | 33 P1S1K1 | 48.92                     | .13             | 1.1422 | .0031          | .567   | .153             | .52      | 68.1   |
| 243.-246.                      | 24 N2     | 6.61                      | .08             | 1.1498 | .0136          | 1.988  | .683             | .24      | 105.4  |
| 252.-258.                      | 26 M2     | 35.53                     | .08             | 1.1835 | .0027          | 2.466  | .129             | 1.67     | 66.3   |
| 267.-277.                      | 21 S2K2   | 16.80                     | .07             | 1.2033 | .0048          | .980   | .226             | .67      | 25.6   |
| 335.-375.                      | 16 M3     | .36                       | .03             | .9579  | .0885          | -6.218 | 5.203            | .06      | -138.0 |
| STANDARD DEVIATION             |           | D                         | 2.73            | SD     | 1.60           | TD     | .66              | MICROGAL |        |
| 01/K1                          |           | 1.0177                    | 1-01/1-K1       | 1.1418 | M2/01          | 1.0182 |                  |          |        |
| CENTRAL EPOCH TJJC = 24460C3.0 |           |                           |                 |        |                |        |                  |          |        |

## TRANS EUROPEAN PROFILE

## STATION BRUXELLES

STATION 0201 BRUXELLES-UCCLE COMPOSANTE VERTICALE BELGIQUE  
50 47 55 N 04 21 29 E H 101 M P 4M D 90KM 981 117 301  
BASSIN EOCENE DE BRUXELLES SUR LE CAMBRIEN DU MASSIF DU BRABANT.  
SABLES LUTETIENS

SABLES LUTTIENS.  
OBSERVATOIRE ROYAL DE BELGIQUE DEPT.1 P.MELCHIOR  
INSTITUTO DI ASTRONOMIA Y GEODESIA DEL C.N.R.,UNIV.COMPLUTENSE MADRID,R.VIEIRA  
GRAVIMETRE LA 'COSTE-ROMBERG 665,ASSERVISSEMENT ELECTRONIQUE M.VAN RUYMBEKE,  
AJUSTEMENT DE LINEARITE PAR METHODE SATO-HARRISON

CALIBRATION LA COSTE - BOMBERG

## **INSTALLATION**

**E. LAURENT - J. JEAN-ZHOU KUNGEN**

LEAST SQUARE ANALYSIS / VENEDIKOV FILTERS ON 48 HOURS / PROGRAMMING B.DUCARME  
POTENTIAL CARTWRIGHT-TAYLER-EDDEN / COMPLETE DEVELOPMENT  
COMPUTING CENTER INTERNATIONAL CENTER FOR EARTH TIDES/FAGS/ BRUSSELS  
COMPUTER SPERRY-UNIVAC 1100/81 PROCESSED ON 65/2/25

**INERTIAL CORRECTION PROPORTIONAL TO THE SQUARE OF ANGULAR SPEEDS  
NORMALISATION FACTOR 1.00729**

6655 641130/a5 123 85 128/a5 128 85 2 1/85 211 85 215/a5 215

TIME INTERVAL 78.5 DAYS 1728 READINGS 4 BLOCKS

| WAVE GROUP<br>ARGUMENT | ESTIMATED AMPL.<br>N WAVE | AMPL.<br>R.M.S. | AMPL.<br>FACTOR | PHASE<br>R.M.S. | PHASE<br>DIFF. | RESIDUE<br>AMPL. | RESIDUE<br>PHASE |            |
|------------------------|---------------------------|-----------------|-----------------|-----------------|----------------|------------------|------------------|------------|
| 133.-139. 24           | Q1                        | 6.70            | .10             | 1.1495          | .0175          | -.752            | .870             | .11 -123.9 |
| 143.-149. 26           | 01                        | 35.36           | .08             | 1.1610          | .0027          | -.108            | .135             | .08 -52.4  |
| 161.-168. 21           | PISIPI                    | 49.33           | .07             | 1.1518          | .0016          | .113             | .061             | .62 9.0    |

|           |    |      |       |     |        |       |       |      |      |      |
|-----------|----|------|-------|-----|--------|-------|-------|------|------|------|
| 243.-248. | 24 | N2   | 6.77  | .04 | 1.1782 | .0068 | 3.469 | .336 | .42  | 77.4 |
| 252.-258. | 26 | M2   | 35.68 | .03 | 1.1887 | .0011 | 2.553 | .052 | 1.79 | 62.6 |
| 267.-277. | 21 | S2K2 | 16.87 | .04 | 1.2081 | .0027 | 1.158 | .129 | .75  | 27.1 |

335.-375. 16 M3 .40 .02 ... 1.0646 .0607 -5.879 3.246 .04 -94.4

STANDARD DEVIATION D 2.43 SD .83 TD .57 MICROGAL  
 01/K1 1.0079 1-01/1-K1 1.0602 M2/01 1.0239  
 CENTRAL EPOCH TJJ= 2446073.0

**END**

**FILMED**

**12-85**

**DTIC**